AD NUMBER

AD819599

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited. Document partially illegible.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors; Critical Technology; 14 AUG 1967. Other requests shall be referred to Air Force Technical Applications Center, Washington, DC 20333. This document contains export-controlled technical data.

AUTHORITY

USAF ltr dtd 28 Feb 1972

LONG RANGE SEISMIC MEASUREMENTS

COMMODORE

20 MAY 1967

Prepared for

AIR FORCE TECHNICAL APPLICATIONS CENTER

Washington, D. C.

14 AUGUST 1967

By

YELKOVNEY, INC.

Under

Project VELA UNIFORM

Sponsored By

ADVANCED RESEARCH PROJECTS AGENCY

Nuclear Test Detection Office

ARPA Order No. 624

DISCLAIMER NOTICE

THIS DOCUMENT IS THE BEST QUALITY AVAILABLE.

COPY FURNISHED CONTAINED A SIGNIFICANT NUMBER OF PAGES WHICH DO NOT REPRODUCE LEGIBLY.

LONG RANGE SEISMIC MEASUREMENTS

COMMODORE

SEISMIC DATA LABORATORY REPORT NO. 193

AFTAC Project No.:	VELA T/6702
Project Title:	Seismic Data Laboratory
ARPA Order No.:	624
ARPA Program Code No.:	5810
Name of Contractor:	TELEDYNE, INC.
Contract No.:	F 33657-67-C-1313
Date of Contract:	2 March 1967
Amount of Contract:	$ 1,736,617
Contract Expiration Date:	1 March 1968
Project Manager:	William C. Dean
	(703) 836-7644

P. O. Box 334, Alexandria, Virginia

AVAILABILITY

This document is subject to special export controls and each transmittal to foreign governments or foreign national may be made only with prior approval of Chief, AFTAC.

This research was supported by the Advanced Research Projects Agency, Nuclear Test Detection Office, under Project VELA-UNIFORM and accomplished under the technical direction of the Air Force Technical Applications Center under Contract F 33657-67-C-1313.

ABLE OF CONTENTS

COMMODORE

EVENT DESCRIPTION

DATE:	20 May 1967
TIME OF ORIGIN:	15:00:00.2Z
YIELD:	
MAGNITUDE:	5.68 ± 0.56
LOCATION:	
SITE:	Nevada Test Site, Area U2am
	GEOGRAPHIC COORDINATES:
	Lat: 37° 07' 49.0" N
	Long: 116° 03'50.0" W
ENVIRONMENT:	
	GEOLOGIC MEDIUM: TUFF
	SURFACE ELEVATION: 4258 ft.
	SHOT ELEVATION: 1773 ft.
	SHOT DEPTH: 2485 ft.
COMPUTED EPICENTER:	ALL STATIONS
	GEOGRAPHIC COORDINATES:
	Lat: 37° 07' 12.0" N
	Long: 116° 09' 36.0" W
	TIME OF ORIGIN: 15:00:013Z
	DEPTH CONSTRAINED TO: 0 km
	EPICENTER SHIFT: 8.6 km S 80° W

Code	Station	Final							
		SPZ	SPR	SPT	LPZ	LPR	LPT	Tape	Timing
MN-NV	Mina, Nevada	+	+	+	+	+	+	*	P
KN-UT	Kanab, Utah	+	+	+	+	+	+	*	P
TFSO	Tonto Forest Seismological Observatory, Arizona	+	+	+	+	+	+	*	P
MO-ID	Mountain Home, Idaho	+	+	+	+	+	+	*	P
UBSO	Uinta Basin, Seismological Observatory, Utah	+	+	+	+	+	+	*	S
BMSO	Blue Mountain, Seismological Observatory, Oregon	+	+	+	+	+	+	*	P
FK-CO	Franktown, Colorado	+	+	+	+	+	+	*	P
LAO	Subarray, AO-10, Montana	+	N	N	+	+	+		P
SA4TX	San Angelo, Texas	+	N	N	+	+	+		P
WMSO	Wichita Mountain Seismological Observatory, Oklahoma	+	+	+	+	+	+	*	P
ST2TX	Streeter, Texas	+	N	N	**	**	**		P
GR2TX	Grit, Texas	+	N	N	+	+	+		P
GR1TX	Grit, Texas	+	N	N	+	+	+		P
ST1TX	Streeter, Texas	**	N	N	+	-	-		P
PG-BC	Prince George, British Columbia, Canada	+	+	+	+	+	+	*	P
RK-ON	Red Lake, Ontario, Canada	+	+	+	+	+	+	*	P
CPSO	Cumberland Plateau, Seismological Observatory, Tenn.	+	+	+	+	+	+	*	P
WH2YK	Whitehorse, Yukon Territory, Canada	+	+	+	+	+	+	*	P
HN-ME	Houlton, Maine	+	+	+	+	+	+	*	P
SV3QB	Schefferville, Quebec, Canada	+	+	+	+	+	+	*	P
NP-NT	Mould Bay, Northwest Territories, Canada	+	+	+	+	+	+	*	P

I	Inoperative	+	Signal
N	No Instrument	-	No Signal
P	Primary Timing	*	Magnetic Tape Available
S	Secondary Timing	**	Magnification Unreliable

Station Status Report - COMMODORE

Table 1



Recording Stations and Signals Received

Figure 1

INTRODUCTION

A long range seismic measurements (LRSM) program and several larger seismographic observatories were established under VELA-UNIFORM to record seismological data resulting from natural seismic activity and a planned series of U. S. underground nuclear tests. The LRSM teams are mobile and occupy locations selected to provide optimum data from events of special interest; the observatories are permanent installations as follows:

Wichita Mountains Seismological Observatory (WMSO)
Lawton, Oklahoma

Uinta Basin Seismological Observatory (UBSO)
Vernal, Utah

Tonto Forest Seismological Observatory (TFSO)
Payson, Arizona

Large Aperture Seismic Array (LASA)
Billings, Montana

The purpose of this report is to provide an analysis of data resulting from the COMMODORE event recorded by the LRSM teams and the VELA observatories and a preliminary summary of data reported by other permanent and temporary seismographic stations.

INSTRUMENTATION AND PROCEDURE

The instrumentation at each of the LRSM locations consists of three-component short-period and three-component long-period seismographs. In general, data are recorded on 35 millimeter film

and on one-inch 14 channel magnetic tape, although recently more portable instrumentation has been incorporated which records only on magnetic tape. The stations are all equipped to record WWV continuously to provide accurate time control. Calibration is accomplished once each day and just prior to each shot at the operational settings. Pertinent information useful for analysis of LRSM data is available to qualified users of this data and is contained in Technical Report 65-43, "Interpretation and Usage of Seismic Data, LRSM Program." General information on LRSM van and portable system equipment and operation is given in Technical Report 66-27, "The LRSM Mobile Seismological Laboratory," and 65-74, "A Portable Seismograph." Copies of these reports may be obtained from DDC. The AD control number of Technical Report 66-27 is 480343. All the observatories have both long-period and short-period, three-component instrumentation, in addition to their other specialized facilities.

Station information is presented in Appendix I(A). This includes the station name and code; the geographic coordinates; the distances and azimuths involved; the station elevations; and the type of instruments in use at each location. Representative instrumental response curves are shown in Appendix II(B), II(C), and II(D).

The procedures used in measuring amplitudes reported herein are illustrated in Appendix II(A) and the unified magnitude is calculated as shown in Appendix I(B). The distance factors (B) beyond 16° are

from Gutenberg and Richter*. For distance less than 16° values were read from a curve in the Gutenberg and Richter paper back to 10° and then extrapolated to 2°, using an inverse cube relationship. An additional magnitude for less than 16° was computed using a method described by Evernden**. (Figure 3)

A standard hypocenter location program for a digital computer is used to determine the location using data from all stations analyzed. Best-fit values of latitude, longitude, and time of origin are determined statistically by a least squares technique. This utilizes a Jeffreys-Bullen travel-time curve as modified by Herrin in 1961 on the basis of Pacific surface-focus recordings. Precision of the computation is limited primarily by the accuracy of arrival times, the validity of the standard travel-time curve, and by local velocity deviations. This method is based on P-wave arrivals with depth constrained to zero.

DATA AND RESULTS (LRSM AND VELA OBSERVATORIES)

The parameters of the COMMODORE event and a summary of the seismic evaluation is shown on the Event Description page. The operational status of the 21 LRSM stations and observatories is given in Table I, and illustrated in Figure 1.

*Gutenberg, B. and Richter, C. F., Magnitude and Energy of Earthquakes Ann. Geofis., 9 (1956), pp. 1-15.

**Evernden, J. F., Magnitude Determination at Regional and Near Regional Distances in the United States, AFTAC/VELA Seismological Center Technical Report VU-65-4A, (1965), pp. 6,13.

Table 2 summarizes the measurements made of the principal phases from the COMMODORE event at the LRSM and VELA stations. Included are the Pn and P arrival times, the maximum amplitudes (A/T) of Pn or P motion and other phases as seen on the short-period instruments. Long-period Love and Rayleigh wave motion are also tabulated in (A/T) form. In addition, individual station Rayleigh wave areas (mm^2) is indicated as measured on the LPZ only. Although reduced to 1K magnification, they have not been normalized to any magnitude. Twenty-one stations recorded short-period and long-period signals from this event.

The unified magnitudes determined from the LRSM and VELA observatories are shown in Figure 2. The average magnitude is 5.68 ± 0.56. The adjusted unified magnitude is 5.41 ± 0.55 and is shown in Figure 3.

The travel-time residuals from the Pn and P phases are shown in Figure 4. Figures 5 through 9 illustrate plots of the amplitudes of P, Pg, Lg, LQ, and LR.

Attached to the report are illustrative seismograms showing the signals recorded at four stations. The most distant station analyzed that recorded COMMODORE was NP-NT at a distance of 4364 kilometers.

Code	Station	Distance (km)	Inst.	Magnification (k) Film x 10	Phase	Observed Travel Time (min)	Observed Travel Time (sec)	Period T (sec)	Maximum Amplitude A/T	Magnitude (m) mb	Magnitude (m) Ms	Area(mm^2) LPZ
MN-NV	Mina, Nevada	234	SPZ	0.296	Pn		36.2	0.6	4846	5.94	5.63	
			SPZ	0.296	Pg		38.7	0.5	23,236			
			SPT	0.415	Lg			0.6	45,053			
			LPZ	0.463	LR			10.0	17,893			863.93
			LPZ	0.463	e	9	55	11.0	5382			
MN-UT	Kanab, Utah	288	SPZ	0.344	Pn		43.2	0.6	3424	6.03	5.77	
			SPZ	0.344	e		44.5	0.6	4467			
			SPZ	0.344	e		48.0	0.5	11,576			
			SPZ	0.344	Pg		49.1	0.6	18,779			
			SPT	3.34	Lg			0.8	25,967			
			LPZ	0.817	LR			9.0	4125			122.40
			LPZ	0.817	e	01	01	(11.0)	(109)			
TFSO	Tonto Forest Seismological Observatory, Arizona	536	SPZ-60	5.5	Pn	1	15.1	0.3	477	6.03	5.74	
			SPZ-60	5.5	e	1	21.4	0.5	346			
			SPZ-60	1.0	Lg	1	29.1	0.75	1966			
			SPN	1.0	Lg			1.3	1419			
			SPZ	1.0	Lg			1.3	2995			
					LR			---	---			
			LPZ	4.0	e	11	30	16.0	111			
MD-ID	Mountain Home, Idaho	660	SPZ	16.89	Pn	1	30.8	0.45	423	6.22	6.00	
			SPZ	16.89	Pg	1	(49.0)	(0.4)	(5131)			
			SPT		Lg			---	---			
			LPZ	8.26	LQ			11.0	(3543)			
			LPZ	1.28	LR			12.0	2510			342.31
			LPZ	13.9	e	12	22	(12.0)	(341)			
UBSO	Uinta Basin Seismological Observatory, Utah	667	SPZ-10	5.0	Pn	01	33.2	0.9	1327	6.72	6.59	
			SPZ-10	5.0	e	01	34.2	0.7	1007			
			SPZ-10	5.0	Pg	01	50.4	0.8	1610			
			SPN	0.9	Lg			1.2	5474			
			SPZ	0.93	Lg			1.2	3632			
			LPZ	2.25	LQ			14.0	(111)			
			LPZ		LR			---	---			
			LPZ	1.08	e	12	23	15.0	113			
BMSO	Blue Mountain Seismological Observatory, Oregon	864	SPZ-3	25.0	Pn	01	56.5	0.45	96.4	5.93	5.66	
			SPZ-3	25.0	e	01	59.8	0.6	140			
			SPZ-3	25.0	Pg	02	23.4	---	---			
			SPN		Lg			---	---			
			SPZ		Lg			---	---			
			LPZ	1.0	LR			15.0	742			420.00
			LPZ	8.8	e	13	25	15.0	108			
FR-CO	Frenktown, Colorado	1049	SPZ	30.0	Pn	02	19.4	(0.8)	(124)	(6.33)	(4.86)	
			SPZ	30.0	e	02	32.0	0.6	137			
			SPZ	30.0	Pg	02	59.5	1.2	1111			
			SPT	29.45	Lg			1.8	2495			
			LPT	4.2	LQ			12.0	2190			
			LPZ	0.627	LR			11.0	4116			598.72

			LPE	1.0	LR			15.0	742			420.00
			LPE	8.8	e	13	25	15.0	108			
FR-CO	Frankstown, Colorado	1049	SPZ	30.0	Pn	02	19.4	(0.8)	(124)	(6.22)	(4.86)	
			SPZ	30.0	e	02	32.0	0.6	137			
			SPZ	30.0	Pg	02	59.5	1.2	3111			
			SPZ	29.45	Lg			1.8	2495			
			LPZ	4.2	LQ			12.0	2190			
			LPZ	0.627	LR			11.0	6116			398.72
			LPZ	0.627	e	14	25	12.0	452			
LAO	Sahwrray, AO-10 Monte...	1338	SPZ	87.7	Pn	02	52.8	(1.0)	(31.9)	(5.60)	(4.49)	
			SPZ	87.7	e	02	55.1	0.7	38.6			
			SPZ	87.7	e	02	(08.2)	0.9	117			
			SPZ	87.7	e	03	14.5	(1.1)	(159)			
			SPZ	87.7	(Pg)	02	40.6	(0.9)	(129)			
			LPZ		LR			---	---			
[illegible]	San Angelo, Texas	1467	SPZ-2	60.0	P	03	11.5	(1.0)	(154)	(6.12)	(5.22)	
			SPZ-2	60.0	e	03	17.4	1.0	106			
			SPZ-2	60.0	PP	03	22.6	1.0	142			
			SPZ-2	60.0	e	03	31.4	1.2	159			
			SPZ-2	60.0	Pg	04	02.8	1.1	(354)			
			LPZ	1.25	LQ			(13.0)	(384)			
			LPZ	1.35	LR			(12.0)	(2123)			218.09
			SPZ-2	60.0	e	12	17.8	3.4	(833)			
WMO	Wichita Mountain Seismological Observatory, Oklahoma		SPZ-6	10.0	P	03	26.5	1.1	81.6	5.41	5.03	
			SPZ-6	35.0	e	03	34.5	(1.5)	(202)			
			SPZ-6	25.0	e	02	42.6	1.[illegible]	235			
			SPZ-6	25.0	Pg	04	29.5	0.9	216			
			SPE	10.5	Lg			(1.8)	(724)			
			SPE	10.0	Lg			(1.[illegible])	(125)			
			LPE	1.0	LQ			15.0	292			
			LPZ	2.5	LR			15.0	352			280.00
			LPZ	24.0	e	17	23	16.0	40.2			
CPTX	Streeter, Texas	1686	SPZ-1	112	P	03	36.5	0.8	41.2	4.84	4.79	
			SPZ-1	112	e	03	38.1	0.8	55.8			
			SPZ-1	112	e	02	40.9	1.0	100			
			SPZ-1	112	Pg	04	(40.6)	0.8	62.6			
			LPZ	**	LR			12.0	**			
GRTX	Grit, Texas	1689	SPZ-1	472	P	02	37.0	0.8	32.5	4.74	4.70	
			SPZ-1	472	e	02	38.6	0.8	41.0			
			SPZ-2	112	e	03	42.2	1.0	102			
			SPZ-2	112	PP	02	49.7	0.9	51.9			
			SPZ-2	112	e	02	54.2	0.8	42.7			
			SPZ-2	112	(Pg)	04	50.9	1.2	104			
			LPZ	9.05	LQ			15.0	226			
			LPZ	1.65	LR			13.0	1054			215.15
			SPE-1	472	e	16	05.8	2.4	224			
			LPZ	9.2	e	17	51	12.0	125			

Code	Station	Distance (km)	Inst.	Amplification (k) Film x 10	Phase	Observed Travel Time (min)	Observed Travel Time (sec)	Period T (sec)	Maximum Amplitude A/T	Magnitude (m) mb	Magnitude (m) ms	Area (mm^2) LPZ
GRIXK	Grit, Texas	1692	SPZ-1	122.5	P	03	37.4	0.8	38.7	4.80	4.73	
			SPZ-1	122.5	e	03	39.3	0.7	36.1			
			SPZ-1	122.5	(Pg)	04	41.8	1.2	152			
			LPT	0.5	LQ			15.0	336			
			LPZ	0.5	LR			12.0	1159			180.00
			LPZ	0.5	e	18	00	(12.0)	(151)			
STIXK	Streeter, Texas	1696	SPZ-1	**	P	03	37.6	0.9	**			
			SPZ-1	**	e	03	42.4	0.8	**			
			SPZ-1	**	(Pg)	04	41.8	0.8	**			
			LPZ	0.17	LR			12.0	1519			176.47
PG-BC	Prince George, British Columbia, Canada	1940	SPZ	54.2	P	04	06.4	1.4	187	5.06		
			SPZ	54.2	e	04	09.5	1.3	511			
			SPZ	54.2	s	04	13.1	1.3	321			
			SPZ	54.2	PP	04	22.7	1.2	187			
			LPR	47.4	S	07	24	20.0	7.3			
			SPR	54.7	Lg			1.8	253			
			SPT	56.9	Lg			1.8	177			
			LPR	47.4	LQ			13.0	209			
			LPT	43.8	LQ			13.0	204			
			LPZ	5.6	LR			13.0	474			116.07
			LPZ	5.6	e	19	33	12.0	104			
RK-ON	Red Lake, Ontario, Canada	2340	SPZ	8.85	P	04	43.4	0.9	713	5.95		
			SPZ	8.85	e	05	3.3	1.1	199			
			LPT	51.9	S	08	37	11.0	36.7			
			SPT	8.92	Lg			(1.6)	(183)			
			LPT	51.9	LQ			12.0	163			
			LPZ	9.5	LR			12.0	391			125.26
			LPZ	93.0	e	21	37	12.0	102			
CPNO	Cumberland Plateau Seismological Observatory, Tenn.	2730	SPZ	40.0	P	05	21.8	0.85	115	5.47		
			SPZ	40.0	e	05	23.4	0.9	184			
			LPN	4.0	S	09	41	(15.0)	(22.9)			
			LPZ	2.6	S	09	41	15.0	44.6			
			SPN		Lg			---	---			
			LPN	4.0	LQ			17.0	83.3			
			LPZ	2.0	LR			15.0	824			350.00
			LPZ	2.0	e	23	(25)	12.0	158			
WHIYK	Whitehorse, Yukon Territory Canada	2942	SPZ	47.4	P	05	38.9	1.0	36.9	5.02		
			SPZ	47.4	e	05	40.9	0.85	41.4			
			SPZ	47.4	PP	06	28.0	1.2	36.3			
			SPZ	47.4	PcP	09	(04.2)	0.7	5.4			
			SPT	36.7	Lg			(2.6)	(151)			
			LPT	12.2	LQ			18.0	130			

			LPE	4.0	LQ			17.0	83.3				
			LPE	2.0	LR			15.0	824				350.00
			LPE	2.0	•	23	(25)	12.0	158				
WHSYK	Whitehorse, Yukon Territory Canada	2942	SPE	47.4	P	05	38.9	1.0	36.9	5.02			
			SPE	47.4	•	05	40.9	0.85	41.4				
			SPE	47.4	PP	06	28.0	1.2	36.3				
			SPE	47.4	PcP	09	(04.2)	0.7	5.4				
			SPT	36.7	Lg			(2.6)	(151)				
			LPT	17.2	LQ			18.0	120				
			LPE	1.94	LR			14.0	590				256.44
			LPE	19.3	•	25	11	15.0	43.5				
BM-ME	Houlton, Maine	4065	SPE	40.7	P	07	07.7	1.3	222	5.89			
			SPE	40.7	•	07	20.0	1.0	43.0				
			SPE	40.7	•	07	23.6	0.95	39.3				
			SPE	40.7	PP	08	(28.1)	1.4	43.8				
			SPE	40.7	PcP	09	(30.6)	0.8	13.0				
			LPT	40.9	LQ			(15.0)	(183)				
			LPE	1.88	LR			15.0	229				119.68
			LPE	20.8	•	30	45	17.0	36.5				
SV3QB	Schefferville.Quebec Canada	4186	SPE	54.4	P	07	15.9	1.2	240	5.88			
			SPE	54.4	•	07	18.0	1.0	239				
			SPE	54.4	•	07	20.2	1.0	115				
			SPE	54.4	PP	08	39.8	0.8	30.4				
			SPR	59.0	Lg			(1.?)	(49.0)				
			SPT	56.2	Lg			(1.5)	(48.0)				
			LPR	28.6	LQ			14.0	62.5				
			LPT	26.2	LQ			13.0	55.9				
			LPE	17.9	LR			14.0	264				149.72
NP-NT	Mould Bay, Northwest Territories,Canada	4364	SPE-1	134.0	P	07	30.4	0.85	161	5.61			
			SPE-1	134.0	•	07	33.5	1.0	59.7				
			SPE-1	134.0	PP	08	59.6	1.40	107				
			SPE-1	134.0	PcP	09	38.6	0.8	21.5				
			SPE-1	134.0	•	09	40.2	1.0	31.7				
			SPT	105.0	S	13	27.0	(1.4)	(43.5)				
			SPT	105.0	Lg			2.8	283				
			LPT	9.58*	LQ			17.0	139				
			LPE	11.47*	LR			16.0	295				209.21

A/T um/sec
() Doubtful Values or Phases
• Measurements Made from Playouts
—— Maximum Amplitudes Clipped on Film and Tape
** Magnification Unreliable


UNIFIED MAGNITUDE
9.0
8.0
7.0
6.0
5.0
4.0
3.0
2.0
0
1000
2000
3000
4000
5000
DISTANCE (km)
DISTANCE = 16°
UBO
MO
FK
KN
TFO
BMO
SA 4
MN
RK
AVERAGE MAGNITUDE Δ < 16° 5.75 ± 0.63
AVERAGE MAGNITUDE 5.68 ± 0.56
HN
SV3
LAO
WMO
GPO
NP
AVERAGE MAGNITUDE Δ > 16° 5.55 ± 0.39
ST 2
GR 1
GR 2
PG
WH 2
UNIFIED MAGNITUDES
for
COMMODORE

Figure 2


UNIFIED MAGNITUDE
DISTANCE (km)
DISTANCE = 16°
UBO
MO
KN
TFO
MN
BMO
SA 4
RK
HN SV3
NP
CPO
PG
WMO
FK
LAO
ST 2
GR 1
GR 2
WH 2
AVERAGE MAGNITUDE Δ < 16° 5.34 ± 0.62
AVERAGE MAGNITUDE Δ > 16° 5.55 ± 0.39
ADJUSTED UNIFIED MAGNITUDE 5.41 ± 0.55
▲ ADJUSTED UNIFIED MAGNITUDE
● STANDARD UNIFIED MAGNITUDE
ADJUSTED UNIFIED MAGNITUDES for COMMODORE

Figure 3


15.0
10.0
5.0
0
-5.0
-10.0
-15.0
T-Δ/8.1 (sec)
JB - Δ/8.1
UBO
BMO
FK
SA4
WMO
MO
TFO
GR2
KN
MN
LAO
ST1 ST2 GR1
PG
RK
T-JB (sec)
CPO
WH 2
HN
HP
SV3
0
1000
2000
3000
4000
5000
DISTANCE (km)
TRAVEL TIME RESIDUALS
for
COMMODORE
Pn & P Data

Figure 4


100,000
10,000
1000
100
10.0
1.0
AMPLITUDE / PERIOD (mμ/sec)
MN
KN
UBO
RK
TFO
MO
SV3
HN
SA4
PG
NP
FK
CPO
BMO
WMO
ST 2
GR 1
WH 2
LAO
GR 2
1/R 3
AMPLITUDES of Pn & P
COMMODORE
Maximum Motion
Vertical Component
100
1000
10,000
100,000
DISTANCE (km)

Figure 5


100,000
10,000
1000
100
10.0
1.0
AMPLITUDE / PERIOD (mμ/sec)
MN
KN
LIO
TFO
UBO
FK
SA 4
WMO
GR 1
LAO
GR 2
ST 2
1/R3
100
1000
10,000
100,000
DISTANCE (km)
AMPLITUDES of Pg
COMMODORE
Maximum Motion
Vertical Component

Figure 6


100,000
10,000
1000
100
10.0
1.0
AMPLITUDE / PERIOD (mμ/sec)
MN
IGN
UBO
TFO
FK
WMO
PG
NP
RK
WH 2
HN
SV 3
R^3
AMPLITUDES of Lg
COMMODORE
Maximum Motion
Horizontal Component
100
1000
10,000
100,000
DISTANCE (km)

Figure 7


100,000
10,000
1000
100
10.0
1.0
AMPLITUDE / PERIOD (mμ/sec)
100
1000
10,000
100,000
DISTANCE (km)
MO
FK
SA 4
WMO
GR 1
GR 2
PG
RK
HN
NP
UBO
WH 2
CPO
AMPLITUDES of LQ
COMMODORE
Maximum Motion
Horizontal Component

Figure 8


100,000
10,000
1000
100
10.0
1.0
AMPLITUDE / PERIOD (mμ/sec)
MN
KN
FK
MO
SA 4
ST 1
GR 1
GR 2
BMO
CPO
WMO
WH 2
PG
RK
N
SV3
HN
AMPLITUDES of LR
COMMODORE
Maximum Motion
Vertical Component
100
1000
10,000
100,000
DISTANCE (km)

Figure 9

Code	Station	Distance (km)	Geographic Latitude	Geographic Longitude	Elev. (km)	Computed Azimuth		Installed Azimuth		Large or Small SP	LP Inst.
						Epi. Sta.	Sta. Epi.	Radial	Tang.		
NE-NV	Mina, Nevada	234	38°26'10" N	118°08'53" W	1.52	309°	128°	308°	38°	L	X
NE-UT	Kanab, Utah	288	37°01'22" N	112°49'39" W	1.74	91°	273°	95°	185°	L	X
TFSO-Z60*	Tonto Forest Seismological Observatory, Arizona	536	34°17'12" N	111°16'03" W	1.49	125°	307°	90°	0°	JM	X
NO-ID	Mountain Home, Idaho	660	43°04'19" N	116°15'56" W	0.79	359°	178°	359°	89°	L	X
UBSO-Z10*	Uinta Basin Seismological Observatory, Utah	667	40°19'18" N	109°34'07" W	1.60	56°	240°	90°	0°	JM	X
BMSO-Z3*	Blue Mountain Seismological Observatory, Oregon	864	44°50'56" N	117°18'20" W	1.19	353°	173°	0°	90°	JM	X
FK-CO	Franktown, Colorado	1049	39°35'12" N	104°27'42" W	1.80	71°	259°	79°	169°	L	X
LAO*	Subarray, AO-10, Montana	1338	46°41'19" N	106°13'20" W	0.90	34°	221°	90°	0°	HSZ	X
SA4TX	San Angelo, Texas	1466	31°49'29" N	101°25'29" W	0.79	109°	298°	118°	208°	Geotech	X
WMSO-Z6*	Wichita Mountain Seismological Observatory, Okla.	1597	34°43'05" N	98°35'21" W	0.51	94°	285°	90°	0°	JM	
ST2TX	Streeter, Texas	1606	30°47'32" N	99°26'52" W	0.58	110°	299°	119°	209°	Geotech	X
GR2TX	Grit, Texas	1689	30°47'11" N	99°24'58" W	0.55	110°	299°	119°	209°	Geotech	X
GR1TX	Grit, Texas	1692	30°46'40" N	99°23'03" W	0.52	110°	299°	119°	209°	Geotech	X
ST1TX	Streeter, Texas	1696	30°45'08" N	99°21'20" W	0.52	110°	299°	119°	209°	Geotech	X
PG-BC*	Prince George, British Columbia, Canada	1940	53°52'50" N	122°31'23" W	0.91	347°	163°	110°	200°	L	X
RK-ON	Red Lake, Ontario, Canada	2340	50°50'20" N	93°40'20" W	0.37	42°	238°	58°	148°	S	X
CPSO-Z8*	Cumberland Plateau Seismological Observatory, Tenn.	2731	35°35'41" N	85°34'13" W	0.57	84°	283°	90°	0°	JM	X
WHZYK	Whitehorse, Yukon Territory, Canada	3242	60°41'41" N	134°58'02" W	0.85	339°	144°	325°	55°	L	X
HN-ME	Houlton, Maine	4065	46°09'43" N	67°59'09" W	0.21	60°	273°	93°	183°	S	X
SV3QB*	Schefferville, Quebec, Canada	4186	54°48'39" N	66°45'00" W	0.58	46°	263°	139°	229°	S	X
MP-NT	Mould Bay, Northwest Territories, Canada	4364	76°15'08" N	119°22'18" W	0.06	359°	176°	356°	86°	JMS	X

* Seismometer Not Oriented Toward NTS

Recording Site Information
Appendix I(A)

Unified Magnitude: $m = \log_{10} (A/T), + B$

where

A = zero to peak ground motion in millimicrons
$= \frac{(mm)\ (1000)}{K}$

T = signal period in seconds

B = distance factor (see Table below)

mm = record amplitude in millimeters zero to peak

K = magnification in thousands at signal frequency

Table of Distance Factors (B) for Zero Depth

Dist (deg)	B	Dist (deg)	B	Dist (deg)	B	Dist (deg)	B
0°	-	27°	3.5	54°	3.8	80°	3.7
1	-	28	3.6	55	3.8	81	3.8
2	2.2	29	3.6	56	3.8	82	3.9
3	2.7	30	3.6	57	3.8	83	4.0
4	3.1	31	3.7	58	3.8	84	4.0
5	3.4	32	3.7	59	3.8	85	4.0
6	3.6	33	3.7	60	3.8	86	3.9
7	3.8	34	3.7	61	3.9	87	4.0
8	4.0	35	3.7	62	4.0	88	4.1
9	4.2	36	3.6	63	3.9	89	4.0
10	4.3	37	3.5	64	4.0	90	4.0
11	4.2	38	3.5	65	4.0	91	4.1
12	4.1	39	3.4	66	4.0	92	4.1
13	4.0	40	3.4	67	4.0	93	4.2
14	3.6	41	3.5	68	4.0	94	4.1
15	3.3	42	3.5	69	4.0	95	4.2
16	2.9	43	3.5	70	3.9	96	4.3
17	2.9	44	3.5	71	3.9	97	4.4
18	2.9	45	3.7	72	3.9	98	4.5
19	3.0	46	3.8	73	3.9	99	4.5
20	3.0	47	3.9	74	3.8	100	4.4
21	3.1	48	3.9	75	3.8	101	4.3
22	3.2	49	3.8	76	3.9	102	4.4
23	3.3	50	3.7	77	3.9	103	4.5
24	3.3	51	3.7	78	3.9	104	4.6
25	3.5	52	3.7	79	3.8	105	4.7
26	3.4	53	3.7				







Detail Showing Allowance For Line Width



Pick <u>time</u> of <u>Pn</u> at beginning of "a" half cycle.

Pick <u>amplitude</u> of <u>Pn</u> as maximum "$d/2$" within 2 or 3 cycles of "c".

Pick <u>amplitudes</u> of <u>Pg</u> and <u>Lg</u> at maximum of corresponding motion.

Seismic Analysis Diagram

APPENDIX II(A)





INSTRUMENT RESPONSE CURVES - LRSM

APPENDIX II(B)





INSTRUMENT RESPONSE CURVE - LASA

APPENDIX II(C)





INSTRUMENT RESPONSE CURVES - OTHER SHORT PERIOD

APPENDIX II(D)

Unclassified
Security Classification

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) TELEDYNE, INC. ALEXANDRIA, VIRGINIA	2a. REPORT SECURITY CLASSIFICATION Unclassified 2b. GROUP ---

3. REPORT TITLE

Long Range Seismic Measurements - COMMODORE

4. DESCRIPTIVE NOTES (Type of report and inclusive dates)

Scientific

5. AUTHOR(S) (Last name, first name, initial)

Clark, Don M.

6. REPORT DATE	7a. TOTAL NO. OF PAGES	7b. NO. OF REFS
August 14, 1967	26	2

8a. CONTRACT OR GRANT NO. F 33657-67-C-1313 b. PROJECT NO. VELA T/6702 c. ARPA Order No. 624 d. ARPA Program Code No. 5810	9a. ORIGINATOR'S REPORT NUMBER(S) 193 9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report) ---

10. AVAILABILITY/LIMITATION NOTICES

This document is subject to special export controls and each transmittal to foreign governments or foreign national may be made only with prior approval of Chief, AFTAC.

11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY
---	ADVANCED RESEARCH PROJECTS AGENCY NUCLEAR TEST DETECTION OFFICE WASHINGTON, D. C.

13. ABSTRACT

An analysis of seismological data from an underground nuclear explosion as a continuing study to provide information to aid in distinguishing between earthquakes and explosions. A table of travel-times and amplitudes of P, Pg, Lg, and surface waves are included along with other unidentified phases.

DD FORM 1 JAN 64 1473

Unclassified
Security Classification

Unclassified

Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Seismic Magnitude Seismic Travel-Time Seismic Amplitude VELA-UNIFORM Nuclear Tests						

INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization *(corporate author)* issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers *(either by the originator or by the sponsor)*, also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

(1) "Qualified requesters may obtain copies of this report from DDC."

(2) "Foreign announcement and dissemination of this report by DDC is not authorized."

(3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through

_____."

(4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through

_____."

(5) "All distribution of this report is controlled. Qualified DDC users shall request through

_____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring *(paying for)* the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as *(TS)*, *(S)*, *(C)*, or *(U)*.

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.

GPO 886-551

Unclassified

Security Classification

COMMODORE

MN-NV

MINA, NEVADA

20 MAY 1967

Δ = 254 km




00:00.CZ
1
2


2
3


3
1
4

COMMODORE

RK-ON

RED LAKE, ONTARIO, CANADA

20 MAY 1967

Δ = 2340 km




4:10.0Z
1
2

2

3


6
7


7
8


8
9


9
10


10
11


11
12





COMMODORE

WH2YK

WHITEHORSE, YUKON TERRITORY
CANADA

20 MAY 1967

Δ= 2942 km




00.0 Z
1
2



2 3


3
4


4
5


5
6


6
7


7
8


8
9


9
10


10
11


11
12





13

14





COMMODORE

SV308

SCHEFFERVILLE, QUEBEC, CANADA

20 MAY 1967

Δ = 4186 km


15:06:40.0 Z
1
2


2
3



3

4


A
5


5
6


6
7


7
8


8
9


9
10


10
11


11
12


12
13


13
14